

MULTIMEDIA DATA/VIDEO PROJECTORS



Feature Packed, Budget Friendly



NEW Mobile XGA Projector

EX240U



XGA 1024x768

2500 LUMENS

2000:1

4000hr Estimated Lamp Life*

29dBA Noise Level*

5.3lbs
Ultra Portable

HDMI

S.R.D. LAMP TOP LOADING

CLOSED CAPTION SUPPORT

A New Definition of Value

Maximize your budget with the new Mitsubishi EX240U—a low cost XGA projector that offers features you'd expect in higher priced models. High-end features on the EX240U include an HDMI connection as well as a 6-segment color wheel for a rich and vivid spectrum. With the EX240U, your technology won't be limited by your budget

DLP Technology

DLP projectors have long been a classroom's best choice. With filter-free design comes reduced maintenance, saving both time and costs—lowering the overall lifetime operating cost of the unit while maintaining better longevity and durability.

Light & Bright

The EX240U weighs only 5.3lbs offering excellent portability or easy light-weight installations while showing an impressive brightness of 2500lm. From meeting rooms to classrooms, clear images are displayed even with ambient light. With an estimated lamp life of up to 4000 hours (in low mode), you'll be shining for quite a while.

3D-Ready—Enjoy the Future Today

Future-proof your installation with the 3D-Ready Mitsubishi EX240U! Immersive, interactive 3D presentations are the future of instructional education, and with the EX240U—you'll be ready. The 3D video content must be designed in field sequential format, played in a 3D capable computer and active shutter glasses are required.

Crestron RoomView™

The EX240U is equipped with a RJ-45 terminal for LAN connectivity and remote operation when connected to a network. Compatibility with Crestron® RoomView™ software enables integrated control of up to 250 projectors including power on/off control, message display on multiple projectors and confirmation of lamp service hours. RoomView automates and streamlines several management and technical support functions so you can work more efficiently and provide the best possible support.

ROUTIVIEW LAN PROJECTOR












EX240U Mobile XGA Projector


Input and Output Terminals





- Monitor output
- 2 PC/Component video input
- **3** HDMI
- Serial RS-232C
- **6** LAN (RJ-45)
- 6 Audio input
- Audio output
- 8 S-Video
- Video

Dimensions









Specifications EX240U Display Technology 0.55" 1-Chip DMD 1024 x 768 (Total 786,432 pixels) Contrast Ratio 2000:1 40" - 300" 1.9 - 2.1 4000 hours*3 (Low Mode), 3000 hours*3 (Standard Mode) 640 x 480 - 1600 x 1200, True: 1024 x 768, Sync on Green available NTSC / NTSC 4.43 / PAL (including PAL-M, N) / SECAM / PAL-60 Component Video: 480i/p (525i/p), 576i/p (625i/p), 720p (750p), 1080i/p (1125i/p 60Hz), 1080i/p (1125i/p 50Hz) RGB: mini D-sub 15pin x 2 Video: RCA x 1 + S-VIDEO x 1 Digital: HDMI (Ver1.2) x 1 Audio: Stereo mini jack (ø3.5mm) x 1 RGB: mini D-sub 15pin x 1 Audio: Stereo mini jack (ø3.5mm) x 1 **RS-232C:** D-Sub 9pin x 1 **LAN:** RJ-45 x 1 Speaker Output 2W Mono Dimensions (W x H x D) 11.1" x 3.7" x 9.0" (Not including protrusion) 2.4kg / 5.3lbs Power Requirements AC 100-240V, 50/60Hz

Compliance with ISO21118-2005


All brand names and product names are trademarks, registered trademarks or trade names of their respective holders.

1: Value may vary a few percent from that listed in the chart.

2: The above numbers are approximate, and may be slightly different from the actual measurements.

3: Lamp life specification is an estimate based on information provided by the lamp manufacturer and is not the duration of the warranty. Lamp will shut-off automatically when usage reaches the specified estimated maximum lamp hours.

Screen size and Projection distance



Replacement Lamp (VLT-EX240LP), Ceiling mount (PROJ-UCM-PRO2), Hard shell case (DKT1-ATAC)

Soft carrying bag, Remote control (With 2 batteries), Power cable, VGA(D-sub) cable, User-Manual (CD-ROM), Safety manual, Lens Cap

3-Years of Parts/Labor, 3-Years of Express Replacement Assistance (ERA), 1-year or 500 hours lamp warranty (whichever comes first)

Screen size chart (4:3 aspect ratio)

Screen						Distance from screen (L)				Height	
Diagonal Size		Width (W)		Height (H)		Shortest (Wide)		Longest (Tele)		projected image (Hd)	
inch	cm	inch	cm	inch	cm	inch	m	inch	m	inch	cm
40	102	32	81	24	61	60	1.5	66	1.7	2	6
60	152	48	122	36	91	90	2.3	99	2.5	4	9
80	203	64	163	48	122	120	3.0	132	3.4	5	12
100	254	80	203	60	152	150	3.8	165	4.2	6	15
150	381	120	305	90	229	225	5.7	247	6.3	9	23
200	508	160	406	120	305	300	7.6	330	8.4	12	30
250	635	200	508	150	381	375	9.5	412	10.5	15	38
300	762	240	610	180	457	450	11.4	-	_	18	46

The above numbers are approximate, and may be slightly different from the actual measurements.

Screen size chart (16:9 aspect ratio)

Solder Size Grant (16.6 depost ratio)											
						Distance from screen (L)				Height	
Diagonal Size		Width (W)		Height (H)		Shortest (Wide)		Longest (Tele)		projected image (Hd)	
inch	cm	inch	cm	inch	cm	inch	m	inch	m	inch	cm
40	102	35	89	20	50	66	1.7	73	1.9	6	15
60	152	52	133	29	75	99	2.5	109	2.8	9	22
80	203	70	177	39	100	132	3.4	146	3.7	12	30
100	254	87	221	49	125	166	4.2	182	4.6	15	37
150	381	131	332	74	187	248	6.3	273	6.9	22	56
200	508	174	443	98	249	331	8.4	364	9.3	29	75
250	635	218	553	123	311	414	10.5	455	11.6	37	93
275	699	240	609	135	342	455	11.6	-	_	40	103

The above numbers are approximate, and may be slightly different from the actual measurements.

MITSUBISHI DIGITAL ELECTRONICS AMERICA, INC.

Presentation Products Division Phone: 888.307.0349

www.mitsubishi-presentations.com



MITSUBISHI ELECTRIC SALES CANADA, INC.

Display & Imaging Solutions Division Phone: 905.475.7728 www.mitsubishielectric.ca