

Unbelievable low price. Unbeatable value.

IN110a (SERIES)

The InFocus IN110a Series are not only some of the lowest cost projectors we've ever sold, but also have one of the longest-lasting lamps – for incredibly low total cost of ownership.

These value-packed projectors are easy to buy and built to perform with HDMI input, high brightness, high contrast, and BrilliantColor[™] technology. Plus, their compact design and light weight make them as easy to move around as they are to install.

Why choose the IN110a Series?

- Ultra-low purchase price
- Long life lamp of up to 10,000 hours lowers costs even more
- O High 15000:1 contrast ratio
- Compact and light weight for easy portability
- Accurate and vivid color reproduction with BrilliantColor technology
- HDMI connectivity
- Display 3D content from Blu-ray and PCs

Lowest Total Cost of Ownership

The IN110a Series are not only some of the lowest priced office/classroom projectors we've ever offered, but their lamps can last up to an amazing 10,000 hours. There aren't even any filters to replace. It's an unbeatable value.

High Brightness and High Contrast

The image quality of these projectors will not disappoint. 3000 lumens will give you bright, clear images with the lights on and the 15000:1 contrast ratio adds sharpness with darker blacks and whiter whites.

Preset modes give you the best image quality on a beige wall, whiteboard, blackboard or other surface.

Resolution Options

Choose from a wide range of native resolutions to meet your budget, installation or type of content typically displayed — all the way up to 1080p HD resolution.

Eco Blanking

Instantly dim the screen to divert your audience's attention onto you with the Eco Blanking feature on the remote control.

Activate this feature when the projector isn't being used and lower the lamp's power usage down to 30%. This saves energy and significantly extends the life of the lamp, which saves you money.



IN112a	IN114a	IN116a	IN118HDa
SVGA	XGA	WXGA	1080p
(800 x 600)	(1024 x 768)	(1280 x 800)	(1920 x 1080)
3000 lumens	3000 lumens	3000 lumens	3000 lumens
HDMI 1.4	HDMI 1.4	HDMI 1.4	HDMI 1.4



Connectivity VGA x 2 Composite Video RS232 USB-B (control & firmware)

HDMI 1.4 S-Video 3.5 mm audio in x 2 3.5 mm audio out Monitor out (VGA)

Specifications*

	IN112a	IN114a	IN116a	IN118HDa		
Native Resolution	SVGA 800 x 600	XGA 1024 x 768	WXGA 1280 X 800	1080p 1920 x 1080		
Maximum Resolution	WUXGA 1920 x 1200					
Display Technology	DLP 0.55" SVGA, 800x600	DLP 0.55" XGA, 1024x768	DLP 0.65" WXGA, 1280x800	DLP 0.65" 1080, 1920x1080		
Brightness		3000 lumens Normal Mod	e (2800 lumens Low Power)			
Lamp Life**	5,000 ho	urs (Normal Mode), 6,000 hours (Low Power), 10,000 hours (Eco Bla	anking***)		
Lamp Power	190W (Normal Mode), 160W (Low Power), 57W (Eco Blanking)					
Contrast Ratio	15000:1					
Color Wheel	6 Segment, 2x Speed					
Audible Noise	30 dB Normal Mode (29 dB Low Power)					
Computer Compatibility		PC, MAC				
Projection Offset	1	15%		17%		
Keystone Correction	± 40° vertical					
Lens Type	Manual zoom and focus					
Lens - Throw Ratio	1.9 - 2.2 (50" @ 2m)		1.5 - 1.8 (99.6" @ 3.2m)			
- Zoom Ratio	1.1:1		1.2:1			
Projection Distance	1.5 - 1	11.9 m	1.41 - 9.66 m	1.0 - 10.0 m		
Image Size		Up to 299 inches (diagonal)				
Aspect Ratio	4:3 (Native), Supports 16:9, 16:10, Auto		16:10 (Native), Supports 4:3, 16:9, Auto	16:9 (Native), Supports 4:3, 16:10, Auto		
Synch - Horizontal Scan Freq		15 - 9	91 kHz	,		
- Vertical Scan Freq	24 - 120 Hz					
Video Compatibility	SDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)					
Number of Colors	1.07 billion					
Audio	2 W mono					
Input Sources	HDMI 1.4, VGA x 2, Composite Video, S-Video, 3.5 mm stereo input x 2, RS232C, USB Type B (control & firmware)					
Output Sources	Monitor out (VGA), Audio out (3.5 mm)					
Control	Projector Keypad, IR Remote, RS232, USB B for presentation control					
Product Dimensions - W×D×H	11.5 x 8.7 x 4.3 in / 292 × 220 × 108 mm					
Product Weight	5.4 lbs / 2.45 kg					
Shipping Dimensions - W×D×H	14.25 x 12 x 7.75 in / 362 × 305 × 197 mm					
Shipping Weight	7.1 lbs / 3.22 kg					
Maximum Altitude	10,000 ft / 3,048 m					
Operating Temperature	32 - 104° F / 0 - 40° C					
3D	Supports 3D content from Blu-ray, cable boxes, dish services, and more (over HDMI) at 144Hz. Also supports PC-based 3D content configured at 1080p running at 120Hz signal. DLP Link 3D glasses required					
Additional Features	Instant on/off (within 100 seconds), Program dimming, Top-loading lamp, Security lock slot, Security bar, User PIN					
Ships with - Accessories	Power cord, VGA cable, Safety instructions, User manual, Remote control					
Warranty	1 year					
Lamp Warranty	6 months					
Accessories Warranty	90 days					
Menu Languages	English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simp. Chinese, Trad. Chinese, Spanish, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic, Vietnamese, Indonesian, Persian, Czech, Romanian, Hungarian					
Approvals	UL and c-UL (US/Canada), FCC (US/Canada), CE (Europe), CCC+CECP (China), KCC (Korea), IRAM (Argentina), NOM (Mexico), PCT/CU/EAC (Russia), PSB (Singapore), SABS (South Africa), SASO (Saudi Arabia), CB, Nemco/GS, KC					

* Product specifications, terms, and offerings are preliminary and subject to change at any time without notice.

** Actual lamp life may vary based on the ambient environment and projector usage. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.

*** Eco Blanking hours are determined by a combination of the projector's use in Normal/Low power modes and while using the Eco Blanking feature.

Optional Accessories

Replacement Lamp (SP-LAMP-086) Universal Ceiling Mount (PRJ-MNT-UNIV) LiteShow Wireless Adapter (INLITESHOW4) LiteShow Mount (PRJ-MNT-LS3) Soft Carry Case (CA-SOFTVAL-2) Extended Warranties (PROJ-EW1YR-V, PROJ-EW2YR-V) Cables and adapters

Warranty

Providing the highest quality products and support is very important to us. The IN110a Series comes standard with a 1-year factory warranty (including parts and labor), 6-month lamp replacement warranty, and 90-day accessories warranty. Extended warranties available.



©2014 InFocus Corporation. All rights reserved. Specifications are subject to change without further notice. InFocus and InFocus Collaboration That Works are either trademarks or registered trademarks of InFocus Corporation in the United States and other countries. DLP, the DLP logo, and the DLP medallion are trademarks of Texas Instruments. All trademarks are used with permission or are for identification purposes only and are the property of their respective companies. InFocus_IN110a_Series_Datasheet_EN_27AUG14.